



Factory Code	Enertec Item Code	Capacity 20/hr Rate	CCA SAE (-18 °C)	Res Cap Minutes	Length mm	Width mm	Height mm	Mass kg	Terminal Layout
--------------	-------------------	---------------------	------------------	-----------------	-----------	----------	-----------	---------	-----------------

ENERTEC

MARINE & LEISURE DEEP CYCLE BATTERIES

674 Deep Cycle (54.105D)	23BAT674D-VAL	105	690	190	330	175	240	21.9	Tapered Terminal
M24MF / G206	13BAT-M24-VAL	70	500	100	259	173	227	18	RHP Tapered
M27MF / G256	13BAT-M27-VAL	100	750	180	306	173	227	23	LHP Tapered

OPTIMA

AGM SPIRAL DEEP CYCLE & HIGH CRANKING BATTERIES

YT S 4,2 (982924)	13BATYTS4/2-OPT	55	765	120	254	175	200	19.5	LHP Tapered
YT S 5,5 (985823)	13BATYTS5/5-OPT	75	975	155	325	165	238	26.5	LHP Tapered

Factory Code	Enertec Item Code	RATED CAPACITY			MIN OF DISCHARGE			Length mm	Width mm	Height mm	Mass kg	Terminal Layout
		20HR	10HR	5HR	25A	75A	100A					

DISCOVER

EV TRACTION DRY CELL 6 VOLT MONOBLOCKS - BATTERIES

(Optional)

EV506A-230	12BAT506A-230-DI	230	210	195	485	130	92	244	185	275	30	M8(SAE)
EVG6A-A	12BATGC6A-A-DIS	220	200	190	475	125	88	260	180	267	30	AM (M8)
EVT6A-A	12BATGT6A-A-DIS	260	240	222	575	155	110	260	180	272	36	M8(AM)
EV305A-A	12BAT305A-A-DIS	330	305	285	770	220	160	295	180	365	49	AM (M8)
EVL16A-A	12BATL16A-A-DIS	390	365	335	915	265	190	295	180	426	55	AM (M8)

DISCOVER

EV TRACTION DRY CELL 12 VOLT MONOBLOCKS - BATTERIES

(Optional)

EV712A-18	12BAT712A-18-DIS	20	19	18	-	-	-	181	77	167	6.3	M5 (F3)
EV512A-24	12BAT512A-24-DIS	26	24	22	31	-	-	166	175	125	9	M5 (F4)
EVU1A-A	12BATU1A-A-DIS	33	31	28	45	12	7	195	130	180	11	F7 (M6)
EV512A-45	12BAT512A-45-DIS	50	45	40	75	18	12	197	165	170	14	M6 (F4)
EV34A-A	12BAT34A-A-DIS	65	60	55	115	28	22	258	167	198	20	SAE (M6)
EV512A-70	12BAT512A-70-DIS	68	64	60	118	33	21	278	174	190	22	SAE (M8)
EV24A-A	12BAT24A-A-DIS	85	78	72	155	38	27	258	172	226	24	AM (M8)
EV27A-A	12BAT27A-A-DIS	100	95	87	195	50	35	308	172	232	29	AM (M8)
EV31A-A	12BAT31A-A-DIS	115	110	96	235	63	42	330	172	236	33	AM (M8)
EV12A-A	12BAT12A-A-DIS	140	130	120	300	80	55	327	180	274	40	AM (M8)
EV512A-150	12BAT512-150-DIS	150	140	130	320	88	60	341	173	288	40	M8
EV185A-A	12BAT185A-A-DIS	230	210	198	490	135	95	386	180	356	63	AM (M8)
EV4DA-A	12BAT4DA-A-DIS	235	220	200	515	140	100	524	225	242	63	AT (M8)
EV8DA-A	12BAT8DA-A-DIS	280	260	240	630	185	130	522	275	242	78	AT (M8)